

## Description

Various pipes and fittings for solvent welding, for fusion welding, with threaded ends and flange connection in different plastic materials.

## Product Features

- Max. working pressure according to material and working conditions
- Temperature range according to material and working conditions
- Diameter 12-315 mm



The pipes and fittings meet the safety requirements of the Pressure Equipments Directive 2014/68/UE (PED) appendix 1 for fluids of the groups 1 and 2



## Materials

PVC-U
PVC-C
PE
PP
PVDF

## Fittings

A wide range of fittings to complete the piping system available in PVC-U, PVC-C, PE, PP, PVDF with the following connections: solvent welding, fusion welding, with threaded ends, stubs and flanges. The product range includes elbows, angles 90°, angles 45°, T-pieces, adaptors, reductions, unions, end connectors, nuts and spigots, hose adaptors, end caps, etc.



## Pipes

Material	Characteristics	Working pressure (bar)	Rod length (m)
PVC-U	Standard (dark-grey)	PN10, PN16	4 - 5
	Transparent	PN10, PN16	5
PVC-C	Standard	PN16	5
PE	Rod	SDR17 (ISO S8) PN10 SDR11 (ISO S5) PN16	5
	Reel	SDR17 (ISO S8) PN10 SDR11 (ISO S5) PN16	50 - 100
PP	Standard	PN10, PN16	5
PVDF	Standard	PN16	5

Additionally InterApp offers mounting materials and spare parts for the entire range.

Visit our Webshop

